

# **Switchgrass**

#### REFERENCE MATERIAL

## **Pedigree**

Institution: Oklahoma State University

Location: Garvin County, OK

Cultivar: Alamo

Harvested: 2012

Received at INL: 2013

Sample Preparation: Ground to pass through a 1-inch

sieve using a Vermeer BG480 grinder

# **Composition**

**Table 1.** Chemical composition<sup>a</sup> of Reference Switchgrass

%Structural Ash	%Extractable Inorganics	%Structural Protein	%Extractable Protein	%Water Extracted Glucan <sup>b</sup>	
1.88	2.07	1.51	0.54	2.28	
%Water Extracted Xylan <sup>b</sup>	%Water Extractives Others	%EtOH Extractives	%Lignin	%Glucan	
0.09	6.68	2.68	16.24	33.21	
%Xylan	%Xylan %Galactan		%Acetic Acid	%Total	
21.65	1.43	3.27	3.07	96.60	

<sup>&</sup>lt;sup>a</sup>Determined using NREL "Summative Mass Closure" LAP (NREL/TP-510-48087)

## **Proximate, Ultimate & Calorimetry**

**Table 2.** Proximate, ultimate, and calorific values for Reference Switchgrass (reported on a dry basis)

Proximate <sup>a</sup>			Ultimate <sup>b</sup>			Calorimetry <sup>c</sup>		
%Volatile	%Ash	%Fixed Carbon	%Hydrogen	%Carbon	%Nitrogen	HHV	LHV	
80.2	4.2	15.6	5.7	47.2	0.5	8077	6749	

<sup>&</sup>lt;sup>a</sup>Proximate analysis was done according to ASTM D 5142-09

<sup>&</sup>lt;sup>b</sup>Determined by HPLC following an acid hydrolysis of the water extractives

<sup>&</sup>lt;sup>b</sup>Ultimate analysis was conducted using a modified ASTM D5373-10 method (Flour and Plant Tissue Method) that uses a slightly different burn profile

<sup>&</sup>lt;sup>c</sup>Heating values (HHV, LHV) were determined with a calorimeter using ASTM D5865-10


### **Elemental Ash**

**Table 3.** Elemental ash composition<sup>a</sup> of Reference Switchgrass

%Al as Al <sub>2</sub> O <sub>3</sub>	%Ca as CaO	%Fe as Fe <sub>2</sub> O₃	%K as K₂O		%Mn as MnO			%Si as SiO₂	%Ti as TiO₂	%S as SO₃
0.25	7.37	1.63	17.55	9.79	0.19	1.61	4.45	53.53	0.01	2.73

<sup>&</sup>lt;sup>a</sup>Determined as described in ASTM standards D3174, D3682 and D6349

#### **Particle Characteristics**



**Figure 1.** Cumulative passing percent of 1-inch Reference Switchgrass determined according to ANSI/ASAE S319.4 using a Ro-Tap test sieve shaker (Model RX-29, W.S. Tyler) and a 15 minute total sieving time. The cumulative passing percentile sieve sizes (e.g.,  $t_{16}$ ) were calculated by interpolation and represent theoretical sieve sizes that would retain 16, 50 or 84% of the particles by mass.

#### **Contact**

For questions regarding biomass material or analytical data please contact Dr. Garold Gresham at garold.gresham@inl.gov or 208-526-6684.